

# ELECTRONIC RELAY

LOW VOLTAGE | RE25 – RE30

## DIMENSIONS


- RE253: 4.10 in. x 4.10 in. x 2.10 in. (104.1 mm x 104.1 mm x 53.3 mm)
- RE306C: 4.76 in. x 4.70 in. x 3 in. (120.9 mm x 119.4 mm x 76.2 mm)

## CONTROL

- pulsed signal (PWM) or all or nothing (on/off) at 24 Vac, 3-32 Vdc signal
- with transformer (RE253T)
- compatible with STE241, T822K1034, T87K1015, D010 and ET180 thermostats
- two additional relays without transformers can be added to the same control circuit as a relay with transformer
- installation of more than 4 relays without transformers to the same thermostat is not recommended

## INSTALLATION


the relay must be installed in an external junction box



RE253C



RE253T



RE306C

PRODUCT	DESCRIPTION	PRICE
RE253C	ELECTRONIC LOW VOLTAGE RELAY [25 A @ 120 V, 208 V, 277 V OR 347 V]	94.50
RE253T	ELECTRONIC LOW VOLTAGE RELAY [25 A @ 208 V, 277 V OR 347 V] (W/TRANSFO)	96.75
RE306C	ELECTRONIC LOW VOLTAGE RELAY [30 A @ 120 V-600 V]	129.00

