

COMMERCIAL & RESIDENTIAL UNIT HEATER

RUH SERIES

OXFORD™
SERIES | SÉRIE

A VERSATILE WORKHORSE

The RUH unit heater is small on price and big on heat. These heavy-duty units are well suited to situations where large amounts of heat must be provided in wide open spaces such as garages, workshops, commercial warehouses and construction sites. This unit has a powerful output up to 5000 W with a voltage of 240/208. The RUH has adjustable louvers that allow you to direct heat right from the source. With or without a built-in thermostat, it provides instant heat. Quiet, lightweight and easy-to-install with a universal wall or ceiling mounting bracket, this unit heater is everything you expect for less. Guaranteed productivity!



INSTANT HEAT

ADJUSTABLE LOUVERS ALLOW YOU TO DIRECT HEAT

THERMAL PROTECTION

WALL OR CEILING INSTALLATION
SUPPORT BRACKET INCLUDED

ENCLOSED & PERMANENTLY LUBRICATED MOTOR

2 KW TO 5 KW MODELS AVAILABLE

IDEAL FOR:

CONSTRUCTION SITE, GARAGE, WORKSHOP, SMALL COMMERCIAL SPACE

COLOUR

textured charcoal

FINISH

epoxy-polyester powdercoat

MANUFACTURING

- 20-gauge steel cabinet
- totally enclosed and factory lubricated motor
- 350 CFM quiet helicoidal fan
- adjustable louvers
- thermal protection with automatic reset

ELEMENT

nichrome element produces instant heat

CONTROL

- built-in thermostat (included with T series)
- wall thermostat (not included)

INSTALLATION

wall or ceiling mounted with universal mounting bracket (included with unit)



TECHNICAL SPECIFICATIONS

WITHOUT CONTROL		BUILT-IN THERMOSTAT		24 V CONTROL		POWER	VOLTAGE	PHASE	FLOW	POWER	THROW DISTANCE		HEAT RISE		WEIGHT	
CODE	PRICE	CODE	CODE	PRICE	WATTS	VOLTS	NB	CFM	BTU/H	M	FT.	°C	°F	KG	LB	
RUH2CHAR	326.00	RUH2TCHAR	RUH2C24CHAR	337.00	2000/1500	240/208	1	350	6826	3	10	27	48	9	20	
RUH3CHAR	331.00	RUH3TCHAR	RUH3C24CHAR	343.00	3000/2250	240/208	1	350	10239	3	10	34	60	9	20	
RUH4CHAR	337.00	RUH4TCHAR	RUH4C24CHAR	349.00	4000/3000	240/208	1	350	13652	3	10	46	82	9	20	
RUH5CHAR	343.00	RUH5TCHAR	RUH5C24CHAR	354.00	5000/3750	240/208	1	350	17065	3	10	64	114	9	20	

TECHNICAL DRAWINGS

